

**ANNEX 17****DRAFT MEASUREMENT REPORTING PROTOCOL FOR BLACK CARBON DETERMINATION** PPR 3/WP.4, ANNEX 1**1. Engine design parameters (to be completed before measurement)****1.1 Engine**

Production year: 2015  
Location: ☒ Testbed  
☐ Ship

**1.2 Engine freshly manufactured**

☒ Yes ☐ No

If no: Documentation of relevant maintenance provided ☐ Yes ☐ No

**1.3 Engine total running hours**

23 [h]

**1.4 Regular maintenance interval**

6000 [h]

**1.5 Hours since last regular maintenance**

- [h]

**1.6 Engine category**

☒ 4-stroke  
☐ 2-stroke

**1.7 Engine fuel type**

☒ Diesel ☐ Gas ☐ Dual fuel

**1.8 Engine max. rated power**

10800 [kW]

**1.9 Mean effective pressure at rated power**

25.8 [bar]

**1.10 Engine speed**

☐ Less than 130 rpm  
☒ 130 or more but less than 2,000 rpm  
☐ 2,000 rpm or more

**1.11 Method of air aspiration**

☐ Naturally aspirated  
☒ Pressure-charged single stage  
☐ Pressure-charged multi stage

**1.12 Injection system**

☐ Conventional  
☒ Common rail

**1.13 Applicable emission limit**

☐ IMO Tier I ☒ IMO Tier II ☐ IMO Tier III  
☐ Others: \_\_\_\_\_

**1.14 Applicable test cycle**

☐ C1 ☐ D2 ☒ E2 ☐ E3  
☐ Others: \_\_\_\_\_

**1.15.1 Specific lubrication oil consumption**SLOC: 0.5 [g/kWh]Breaking-in period: ☐ Finished  
☒ Not finished  
☐ Not applicable**1.15.2 Cylinder liner lubrication**☐ None  
☒ Yes, active at☒ 100% Feed rate: \_\_\_\_\_ [g/h]  
☒ 75% Feed rate: \_\_\_\_\_ [g/h]  
☒ 50% Feed rate: \_\_\_\_\_ [g/h]  
☐ 25% Feed rate: \_\_\_\_\_ [g/h]  
☐ 10% Feed rate: \_\_\_\_\_ [g/h]Breaking-in period: ☐ Finished  
☒ Not finished  
☐ Not applicable**1.15.3 Inlet valve seat lubrication**☐ None  
☒ Yes, active at☒ 100% Feed rate: \_\_\_\_\_ [g/h]  
☒ 75% Feed rate: \_\_\_\_\_ [g/h]  
☒ 50% Feed rate: \_\_\_\_\_ [g/h]  
☐ 25% Feed rate: \_\_\_\_\_ [g/h]  
☐ 10% Feed rate: \_\_\_\_\_ [g/h]**1.16 Exhaust gas treatment device**☒ None ☐ Yes☐ SCR  
☐ Scrubber  
☐ EGR  
☐ Water injection  
☐ Others: \_\_\_\_\_**2. Fuel****2.1 Fuel in use**☐ ULSD ☐ DMX ☒ DMA ☐ DMZ ☐ DMB  
☐ RMA ☐ RMB ☐ RMD ☐ RME ☐ RMG ☐ RMK  
☐ Other: \_\_\_\_\_ acc. standard: ISO 8217:2010☐ Natural Gas☐ Other gases acc. IGF: \_\_\_\_\_☐ Liquid to gas fuel ratio as certified at mode point:100% \_\_\_\_\_  
75% \_\_\_\_\_  
50% \_\_\_\_\_  
25% \_\_\_\_\_  
10% \_\_\_\_\_

**Fuel properties and composition (in use during testing)****2.2 Gas**

Please fill in as far as possible  
most important marked with \*)

Property	Unit / Standard	Actual value	Remark
Methane number*)	[-] / DIN EN 16726		
Lower calorific value*)	[MJ/kg] / ISO 6976		
Higher calorific value	[MJ/kg] / ISO 6976		
Wobbe Indices Ws / Wi	[MJ/m <sup>3</sup> ] / ISO 6976		
Density*)	[kg/m <sup>3</sup> ] / ISO 6976		
Methane*)	wt.-% [kg/kg] / ISO 6974 or DIN 51894		
Ethane*)	wt.-% [kg/kg] / ISO 6974 or DIN 51894		
Propane*)	wt.-% [kg/kg] / DIN 51894		
Isobutane*)	wt.-% [kg/kg] / DIN 51894		
N-Butane*)	wt.-% [kg/kg] / DIN 51894		
Pentane	wt.-% [kg/kg] / DIN 51894		
Hexane	wt.-% [kg/kg] / DIN 51894		
Heptane	wt.-% [kg/kg] / DIN 51894		
Nitrogen	wt.-% [kg/kg] / ISO 6974		
Sulphur*)	wt.-% [kg/kg] / ISO 6326-5		
Hydrogen sulfide	wt.-% [kg/kg] / ISO 8819		
Carbon dioxide	wt.-% [kg/kg] / ISO 6974		
Hydrogen	wt.-% [kg/kg] / DIN 51894		
Others			

**2.3 Liquid fuel**

Please fill in as far as possible  
most important marked with \*)  
essential \*\*)

Property	Unit / Standard	Actual value	Remark
Type of fuel	Grade / ISO 8217	DMA	
Flash point*)	[°C] / ISO 2719		
Viscosity @ 40/50°C **)	[mm <sup>2</sup> /s] / ISO 3104	3.9	at 40°C
Density @ 15°C *)	[kg/m <sup>3</sup> ] / ISO 3675 or 12185	843	
Net calorific value (Hu) *)	[J/g] / DIN 51900	43076	
Sulphur content*)	ppm [mg/kg] / ISO 8754 or 14596	<1000	
Ash content*)	ppm [mg/kg] / ISO 6245		
Water content*)	ppm [mg/kg] / ISO 3733	<200	
Carbon content*)	wt.-% [kg/kg] / ASTM D5291	85.5	
Hydrogen content*)	wt.-% [kg/kg] / ASTM D5291	13.7	
Nitrogen content*)	wt.-% [kg/kg] / DIN 51444	<0,1	
Oxygen content*)	wt.-% [kg/kg] / DIN 51732		
Cetane index*)	ISO 4264		
CCAI*)			
FAME content*)	wt.-% [kg/kg] / EN 14078		
Mono aromatic compounds*)	wt.-% [kg/kg] / EN 12916		
Poly aromatic compounds*)	wt.-% [kg/kg] / EN 12916		
Di aromatic compounds	wt.-% [kg/kg] / EN 12916		
Tri aromatic compounds	wt.-% [kg/kg] / EN 12916		
Inorganic constituents (V)	ppm [mg/kg] / ISO 14597 or 8691		
Inorganic constituents (Ni)	ICP		
Carbon residues*)	wt.-% [kg/kg] / ASTM D4530		
Others			

### 3. Lube oil properties and composition (in use during testing; Producers specification can be used)

#### 3.1 Circulation lubrication oil

Please fill in as far as possible

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type	Shell Argina T40	
Grade	Multi / Mono	Mono	
BN	mg KOH/g / ISO 3771	30	
Ash content	wt.-% [kg/kg] / ISO 6245	3.7	
Viscosity	[mm <sup>2</sup> /s] / ASTM D7042	135	at 40°C
Sulphur content	wt.-% [kg/kg] / ISO 20884		

#### 3.2 Cylinder oil

Please fill in as far as possible

Please fill in if applicable

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type		
Grade	Multi / Mono		
BN	mg KOH/g / ISO 3771		
Ash content	wt.-% [kg/kg] / ISO 6245		
Viscosity	[mm <sup>2</sup> /s] / ASTM D7042		
Sulphur content	wt.-% [kg/kg] / ISO 20884		

#### 3.3 Valve seat lubrication oil

Please fill in as far as possible

Please fill in if applicable

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type		
Grade	multi / mono		
BN	mg KOH/g / ISO 3771		
Ash content	wt.-% [kg/kg] / ISO 6245		
Viscosity	[mm <sup>2</sup> /s] / ASTM D7042		
Sulphur content	wt.-% [kg/kg] / ISO 20884		

#### 4. Measurement equipment information (to be completed before measurement) and parameters

##### Measurement instrument

4.1 BC measurement instrument information      Make: AVL      Model: 415S

4.2 Measurement principle      ☐ LII      x FSN      ☐ PAS      ☐ MAAP  
☐ Others: \_\_\_\_\_

4.3 Values reported as      ☐ EC (thermal)      Protocol acc.: \_\_\_\_\_  
☐ rBC  
☐ eBC  
x FSN  
☐ Others: \_\_\_\_\_

4.4 Values reported in unit      ☐  $\text{mg}/\text{m}_n^3$  (wet basis; act.  $\text{O}_2$ -concentration)       $\text{H}_2\text{O}$ -conc.: \_\_\_\_\_ [Vol.-%] (wet)  
☐  $\text{mg}/\text{m}_n^3$  (dry basis; act.  $\text{O}_2$ -concentration)  
☐  $\text{mg}/\text{m}_n^3$  (dry basis; Ref.  $\text{O}_2$ -concentration)       $\text{O}_2$ -conc.: \_\_\_\_\_ [Vol.-%] (dry)  
☐  $\text{mg}/\text{kWh}$  refer to 5.  
x FSN  
☐  $\text{mg}/\text{kg}$  fuel refer to 5.  
☐ Others: \_\_\_\_\_

4.5 Reference conditions      Norm temperature: \_\_\_\_\_ [°C]  
(only if 4.4 is referred to Norm-cubic meters [ $\text{m}_n^3$ ])      Norm pressure: \_\_\_\_\_ [mbar]

4.6 Sampling time / -number      Sampling time of each measurement: automatic mode [s]  
If mean values are reported: Number of consecutive  
measurements at each mode point: 3 [-]  
Acc. manufacturer specification:      x Yes      ☐ No

4.7 BC instrument parameter      Temperature inside measuring cell: 70 [°C]  
Pressure inside measuring cell: ambient [mbar]  
Wavelength(s) used: \_\_\_\_\_ [nm]  
Mass absorption cross section(s) used: \_\_\_\_\_ [ $\text{m}^2/\text{g}$ ]  
Conversion equation(s) used: \_\_\_\_\_  
Repeatability of the instrument used:  $\leq 0.005 \text{ FSN} + 3$  % of measured value  
Reproducibility of the instrument used:  $\leq 0.005 \text{ FSN} + 6$  % of measured value  
Acc. manufacturer specification:      x Yes      ☐ No

Other parameters which could influence the measured values:

Parameter / Correction	Unit

**4.8 BC Instrument Calibration**Date of last calibration: 03/11/2014 (dd.mm.yyyy)

Calibration procedure according manufacturer specification:

x Yes ☐ No ☐ Others: \_\_\_\_\_Calibration including zero point: x Yes ☐ NoUsed medium for zero point calibration: Reflectance standard and clean filterUsed calibration standard: ☐ Synthetic flame soot☐ Printex-U☐ Graphite spark aerosol generator GfG soot☐ Soot with inorganic coatings☐ Soot without inorganic coatings

x Reflectance standards

☐ Others: \_\_\_\_\_

Remark: \_\_\_\_\_

Leakage test performed before or after calibration: x Yes ☐ No ☐ Not applicable**4.9 Sample gas pre-treatment**

Please fill in if applicable

Exhaust gas dilution: ☐ Yes x No

If yes, dilution ratio (1:x) \_\_\_\_\_ at mode point: \_\_\_\_\_ [%]

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Dilution medium: ☐ Ambient air ☐ Exhaust gas☐ Others: \_\_\_\_\_Filtration of the dilution medium before dilution: ☐ Yes ☐ No

Temperature of the dilution medium: \_\_\_\_\_ [°C]

Temperature of the diluted exhaust gas: \_\_\_\_\_ [°C]

Evaporation tube ☐ Yes x NoTemperature \_\_\_\_\_ [°C] acc. manufacturer spec. ☐ Yes ☐ NoCatalytic stripper ☐ Yes x NoTemperature \_\_\_\_\_ [°C] acc. manufacturer spec. ☐ Yes ☐ NoThermo-denuder ☐ Yes x NoTemperature \_\_\_\_\_ [°C] acc. manufacturer spec. ☐ Yes ☐ No

Others: \_\_\_\_\_

**4.10 Sample flow rate/volume**Acc. manufacturer specification: x Yes ☐ NoSample flow rate of the raw exhaust gas: 10 [l/min]

Sample flow rate of the diluted exhaust gas: \_\_\_\_\_ [l/min]

Sample volume of the raw exhaust gas: \_\_\_\_\_ [l]

Sample volume of the diluted exhaust gas: \_\_\_\_\_ [l]

☐ Subkinetic ☐ Isokinetic ☐ Superkinetic x Not applicable

## Sample line and probe

### 4.11 Sample/transfer line

Please fill in if applicable

Use of a sample line: ☒ Yes ☐ No (in situ,...)

Acc. manufacturer specification: ☒ Yes ☐ No

Length of the sample line: 3 [m]

Heated sample line: ☒ Yes ☐ No Temperature: 70 [°C]

Sample line material: Viton

Inner diameter of the sample line: 4 [mm]

Isolated or heated connections between sample line, measurement instrument and probe: ☒ Yes ☐ No

Electrical conductive (sample line material): ☐ Yes ☒ No

Grounded: ☐ Yes ☒ No

Grounding method: -

Backflushing sample line between measurements: ☒ Yes ☐ No

### 4.12 Sample probe

Please fill in if applicable

Use of sample probe: ☒ Yes ☐ No (in situ,...)

Acc. manufacturer specification: ☒ Yes ☐ No

Material: ☒ Stainless steel ☐ Others:

Type/design:

- ☐ Probe with single hole at the end (pipe)
- ☒ Probe with single hole at the end (45° beveled)
- ☐ Multi-hole
- ☐ L-shaped pipe with single hole, opening shielded with preclassifier (e.g. hat)
- ☐ Others:

Direction of the probe opening relative to the exhaust gas flow:

- ☐ With flow ☒ Against flow
- ☐ Others:

Effective cross section of sample hole opening(s) 17.8 [mm<sup>2</sup>]

Backflushing sample probe between measurements: ☒ Yes ☐ No

## Sampling point and probe location

### 4.13 Sample point and probe location

☒ Engine Outlet

☐ Downstream heat exchanger

☐ Downstream exhaust gas treatment device

Treatment device active during measurement

☐ Yes

☐ No

☐ Others:

Distance between engine outlet and sampling point: 6 [m]

Diameter of the exhaust gas pipe: 0.8 [m]

Type of exhaust gas pipe where the sample probe is located:

☒ Straight part of the exhaust gas pipe

☐ Bent part of the exhaust gas pipe

Immersion depth of the sample probe: 0.2 [m]

Orientation of the exhaust gas pipe where the sample probe is located:

☒ Horizontal ☐ Vertical ☐ Others:

Length of straight part of the exhaust gas pipe,

if sample probe is located at straight part of the exhaust gas pipe:

Upstream sample probe: 1 [m]

Downstream sample probe: 3 [m]

Exhaust gas pulsation at the sampling point during measurement:

☒ No

☐ Yes

                     [mbar]

## 5. Determination of engine load, exhaust gas flow, exhaust water content, fuel mass flow, O<sub>2</sub> and CO<sub>2</sub> (if applicable)

5.1 Determination of values, instrument performance and calibration shall be in accordance with the requirements of NOx Technical Code 2008 (NTC 2008) and its applicable appendices

5.2.1 Method of load determination

5.2.2 Estimated accuracy of engine load determination +/- \_\_\_\_\_ [%] of reading

5.3.1 Method of exhaust gas flow determination

5.3.2 Estimated accuracy of exhaust gas flow determination +/- \_\_\_\_\_ [%] of reading

5.4.1 Method of exhaust water content determination

5.4.2 Estimated accuracy of exhaust water content determination +/- \_\_\_\_\_ [%] of reading

5.5.1 Method of fuel mass flow determination

5.5.2 Estimated accuracy of fuel mass flow determination +/- \_\_\_\_\_ [%] of reading

5.6.1 Method of O<sub>2</sub> and CO<sub>2</sub> determination

5.6.2 Estimated accuracy of O<sub>2</sub> and CO<sub>2</sub> determination +/- \_\_\_\_\_ [%] of reading

## 6. Measured values for BC determination (to be completed during measurement; measured values)

Date of measurement (dd.mm.yyyy) 

25/09/2015	25/09/2015	25/09/2015	25/09/2015	25/09/2015
------------	------------	------------	------------	------------

Engine parameters

Measurement at mode points: 

100	85	75	50	25
-----	----	----	----	----

 [%]

	↓	↓	↓	↓	↓	
<b>6.1 Stabilized mode point</b>						
Actual Speed	514	514	500	462	402	[rpm]
Speed variation during measuring	0	0	0	0	0	+/- [%]
Actual Load	10820	9187	8095	5403	2706	[kW]
Load variation during measuring	0.5	0.5	0.5	0.5	0.5	+/- [%]
6.2 Charge air temperature	43.8	41.1	39.8	37.9	34.5	[°C]
6.3 Charge air pressure	3821	2981	2601	1538	421	[mbar] rel
6.4 Exhaust gas temp. at engine outlet	324	311	317	307	376	[°C]
6.5 Exh. gas temp. at sampling point						[°C]
(only if there is a significant difference to the exhaust gas temperature at the engine outlet)						
6.6 Exhaust gas back pressure	30	21	17	11	2	[mbar] rel
6.7 Exhaust gas mass flow	78470	64850	58130	45310	21020	[kg/h]
<b>Ambient conditions</b>						
6.8 Ambient temp. at engine inlet	19	21	22	21	21	[°C]
6.9 Ambient pressure at engine inlet	967	967	967	967	966	[mbar]
6.10 Absolute humidity of ambient air	6.8	6.76	6.78	6.66	6.73	[g/kg]
7. Black Carbon	Reported as (see 4.3):		FSN	Unit (see 4.4):		FSN
7.1 Estimated accuracy of measured value	-	-	-	-	-	+/- [%]
7.2 Black Carbon emission	0.05	0.04	0.06	0.05	0.07	
Remark:	§7.1 not applicable due to no determination acc. to §5					
<b>8. Measurement repeatability Indicators</b>						
8.1 95% confidence interval ( +/- unit measured)						
8.2 Variance						
8.3 Sample size (number of measurements taken)	1	1	1	1	1	