

1.15.3 Inlet valve seat lubrication

X None

☐ Yes, active at

☐ 100%

Feed rate: _____ [g/h]

☐ 75%

Feed rate: _____ [g/h]

☐ 50%

Feed rate: _____ [g/h]

☐ 25%

Feed rate: _____ [g/h]

☐ 10%

Feed rate: _____ [g/h]

1.16 Exhaust gas treatment device

X None

☐ Yes

☐ SCR
☐ Scrubber
☐ EGR
☐ Water injection
☐ Others: _____

2. Fuel

2.1 Fuel in use

X ULSD

☐ DMX
☐ DMA
☐ DMZ
☐ DMB
☐ RMA
☐ RMB
☐ RMD
☐ RME
☐ RMG
☐ RMK

☐ Other: _____ acc. standard: _____
☐ Natural Gas
☐ Other gases acc. IGF: _____
☐ Liquid to gas fuel ratio as certified at mode point:

100% _____
75% _____
50% _____
25% _____
10% _____

Fuel properties and composition (in use during testing)

2.2 Gas

Please fill in as far as possible most important marked with *)

Property	Unit / Standard	Actual value	Remark
Methane number*)	[-] / DIN EN 16726		
Lower calorific value*)	[MJ/kg] / ISO 6976		
Higher calorific value	[MJ/kg] / ISO 6976		
Wobbe Indices Ws / Wi	[MJ/m ³] / ISO 6976		
Density*)	[kg/m ³] / ISO 6976		
Methane*)	wt.-% [kg/kg] / ISO 6974 or DIN 51894		
Ethane*)	wt.-% [kg/kg] / ISO 6974 or DIN 51894		
Propane*)	wt.-% [kg/kg] / DIN 51894		
Isobutane*)	wt.-% [kg/kg] / DIN 51894		
N-Butane*)	wt.-% [kg/kg] / DIN 51894		
Pentane	wt.-% [kg/kg] / DIN 51894		
Hexane	wt.-% [kg/kg] / DIN 51894		
Heptane	wt.-% [kg/kg] / DIN 51894		
Nitrogen	wt.-% [kg/kg] / ISO 6974		
Sulphur*)	wt.-% [kg/kg] / ISO 6326-5		
Hydrogen sulfide	wt.-% [kg/kg] / ISO 8819		
Carbon dioxide	wt.-% [kg/kg] / ISO 6974		
Hydrogen	wt.-% [kg/kg] / DIN 51894		
Others			

2.3 Liquid fuel

Please fill in as far as possible most important marked with *) essential **)

Property	Unit / Standard	Actual value	Remark
Type of fuel	Grade / ISO 8217	DIN EN 590:2014-04	
Flash point*)	[°C] / ISO 2719	55	
Viscosity @ 40/50°C **)	[mm ² /s] / ISO 3104	min 2 / max. 4,5	
Density @ 15°C *)	[kg/m ³] / ISO 3675 or 12185	min 820 / max 845	
Net calorific value (Hu) *)	[J/g] / DIN 51900		
Sulphur content*)	ppm [mg/kg] / ISO 8754 or 14596	max. 10	
Ash content*)	ppm [mg/kg] / ISO 6245	0.01	
Water content*)	ppm [mg/kg] / ISO 3733	200	

Carbon content*)	wt.-% [kg/kg] / ASTM D5291		
Hydrogen content*)	wt.-% [kg/kg] / ASTM D5291		
Nitrogen content*)	wt.-% [kg/kg] / DIN 51444		
Oxygen content*)	wt.-% [kg/kg] / DIN 51732		
Cetane index*)	ISO 4264	min 46	
CCAI*)			
FAME content*)	wt.-% [kg/kg] / EN 14078	max 7	
Mono aromatic compounds*)	wt.-% [kg/kg] / EN 12916		
Poly aromatic compounds*)	wt.-% [kg/kg] / EN 12916		
Di aromatic compounds	wt.-% [kg/kg] / EN 12916		
Tri aromatic compounds	wt.-% [kg/kg] / EN 12916		
Inorganic constituents (V)	ppm [mg/kg] / ISO 14597 or 8691		
Inorganic constituents (Ni)	ICP		
Carbon residues*)	wt.-% [kg/kg] / ASTM D4530		
Others			

3. Lube oil properties and composition (in use during testing; Producers specification can be used)

3.1 Circulation lubrication oil Please fill in as far as possible

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type	SRS Antikorrrol	
Grade	Multi / Mono	Mono	
BN	mg KOH/g / ISO 3771	8.1	
Ash content	wt.-% [kg/kg] / ISO 6245	1.04	DIN 51575
Viscosity	[mm ² /s] / ASTM D7042	11.7	(@100°C) DIN 51 562
Sulphur content	wt.-% [kg/kg] / ISO 20884		

3.2 Cylinder oil Please fill in as far as possible Please fill in if applicable

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type		
Grade	Multi / Mono		
BN	mg KOH/g / ISO 3771		
Ash content	wt.-% [kg/kg] / ISO 6245		
Viscosity	[mm ² /s] / ASTM D7042		
Sulphur content	wt.-% [kg/kg] / ISO 20884		

3.3 Valve seat lubrication oil Please fill in as far as possible Please fill in if applicable

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type		
Grade	multi / mono		
BN	mg KOH/g / ISO 3771		
Ash content	wt.-% [kg/kg] / ISO 6245		
Viscosity	[mm ² /s] / ASTM D7042		
Sulphur content	wt.-% [kg/kg] / ISO 20884		

4. Measurement equipment information (to be completed before measurement) and parameters

Measurement instrument

4.1 BC measurement instrument information

Make: AVL Model: 415 S

4.2 Measurement principle

☐ LII ☒ FSN ☐ PAS ☐ MAAP
☐ Others: _____

4.3 Values reported as

☐ EC (thermal) Protocol acc.: _____
☐ rBC
☐ eBC
☒ FSN
☐ Others: _____

4.4 Values reported in unit

☐ mg/m_n^3 (wet basis; act. O_2 -concentration) H_2O -conc.: _____ [Vol.-%] (wet)
☐ mg/m_n^3 (dry basis; act. O_2 -concentration)
☐ mg/m_n^3 (dry basis; Ref. O_2 -concentration) O_2 -conc.: _____ [Vol.-%] (dry)
☐ mg/kWh refer to 5.
☒ FSN
☐ mg/kg fuel refer to 5.
☐ Others: _____

4.5 Reference conditions

(only if 4.4 is referred to Norm-cubic meters [m_n^3])

Norm temperature: _____ [°C]
Norm pressure: _____ [mbar]

4.6 Sampling time / -number

Sampling time of each measurement: automatic mod [s]
If mean values are reported: Number of consecutive measurements at each mode point: 1 [-]
Acc. manufacturer specification: ☒ Yes ☐ No

4.7 BC instrument parameter

Temperature inside measuring cell: 65 [°C]
Pressure inside measuring cell: 980 [mbar]
Wavelength(s) used: _____ [nm]
Mass absorption cross section(s) used: _____ [m^2/g]
Conversion equation(s) used: _____
Repeatability of the instrument used: (+/-0,005 FSN +3% of value)
Reproducibility of the instrument used: (+/-0,005 FSN +6% of value)
Acc. manufacturer specification: ☒ Yes ☐ No

Other parameters which could influence the measured values:

Parameter / Correction	Unit

4.8 BC Instrument Calibration

Date of last calibration: _____ (dd.mm.yyyy)

Calibration procedure according manufacturer specification:

☒ Yes ☐ No ☐ Others: _____

Calibration including zero point: ☐ Yes ☐ No

Used medium for zero point calibration: _____

Used calibration standard: ☐ Synthetic flame soot
☐ Printex-U
☐ Graphite spark aerosol generator GfG soot
☐ Soot with inorganic coatings
☐ Soot without inorganic coatings
☒ Reflectance standards
☐ Others: _____

Remark: _____

Leakage test performed before or after calibration: ☐ Yes ☐ No ☐ Not applicable

4.9 Sample gas pre-treatment

Please fill in if applicable

Exhaust gas dilution: ☐ Yes ☒ No
If yes, dilution ratio (1:x) _____ at mode point: _____ [%]

_____	_____
_____	_____
_____	_____
_____	_____
_____	_____

Dilution medium: ☐ Ambient air ☒ Exhaust gas
☐ Others: _____

Filtration of the dilution medium before dilution: ☐ Yes ☐ No

Temperature of the dilution medium: _____ [°C]
Temperature of the diluted exhaust gas: _____ [°C]

Evaporation tube ☐ Yes ☒ No
Temperature _____ [°C] acc. manufacturer spec. ☐ Yes ☐ No

Catalytic stripper ☐ Yes ☒ No
Temperature _____ [°C] acc. manufacturer spec. ☐ Yes ☐ No

Thermo-denuder ☐ Yes ☒ No
Temperature _____ [°C] acc. manufacturer spec. ☐ Yes ☐ No
Others: _____

4.10 Sample flow rate/volume

Acc. manufacturer specification: ☒ Yes ☐ No

Sample flow rate of the raw exhaust gas: _____ up to 10 [l/min]

Sample flow rate of the diluted exhaust gas: _____ [l/min]

Sample volume of the raw exhaust gas: _____ [l]

Sample volume of the diluted exhaust gas: _____ [l]

☐ Subkinetic ☐ Isokinetic ☐ Superkinetic ☐ Not applicable

Sample line and probe

4.11 Sample/transfer line Please fill in if applicable

Use of a sample line: ☒ Yes ☐ No (in situ,...)

Acc. manufacturer specification: ☒ Yes ☐ No

Length of the sample line: _____ [m]

Heated sample line: ☒ Yes ☐ No
Temperature: _____ 70 [°C]

Sample line material: _____ Viton _____

Inner diameter of the sample line: _____ 4 [mm]

Isolated or heated connections between sample line, measurement instrument and probe: ☐ Yes ☐ No

Electrical conductive (sample line material): ☒ Yes ☐ No
Grounded: ☒ Yes ☐ No
Grounding method: _____

Backflushing sample line between measurements: ☐ Yes ☐ No

4.12 Sample probe Please fill in if applicable

Use of sample probe: ☒ Yes ☐ No (in situ,...)

Acc. manufacturer specification: ☒ Yes ☐ No

Material: ☒ Stainless steel ☐ Others: _____

Type/design: _____
☐ Probe with single hole at the end (pipe)

- X Probe with single hole at the end (45° beveled)
- ☐ Multi-hole
- ☐ L-shaped pipe with single hole, opening shielded with preclassifier (e.g. hat)
- ☐ Others: _____

Direction of the probe opening relative to the exhaust gas flow:

- ☐ With flow X Against flow
- ☐ Others: _____

Effective cross section of sample hole opening(s) _____ [mm²]

Backflushing sample probe between measurements: X Yes ☐ No

Sampling point and probe location

4.13 Sample point and probe location X Engine Outlet

- ☐ Downstream heat exchanger
- ☐ Downstream exhaust gas treatment device
- Treatment device active during measurement ☐ Yes ☐ No
- ☐ Others: _____

Distance between engine outlet and sampling point: --- [m]

Diameter of the exhaust gas pipe: _____ [m]

Type of exhaust gas pipe where the sample probe is located:

- ☐ Straight part of the exhaust gas pipe
- ☐ Bent part of the exhaust gas pipe

Immersion depth of the sample probe: middle of pipe [m]

Orientation of the exhaust gas pipe where the sample probe is located:

- ☐ Horizontal ☐ Vertical ☐ Others: _____

Length of straight part of the exhaust gas pipe,

if sample probe is located at straight part of the exhaust gas pipe:

Upstream sample probe: _____ [m]

Downstream sample probe: _____ [m]

Exhaust gas pulsation at the sampling point during measurement:

- X No ☐ Yes _____ [mbar]

5. Determination of engine load, exhaust gas flow, exhaust water content, fuel mass flow, O₂ and CO₂

(if applicable)

5.1 Determination of values, instrument performance and calibration shall be in accordance with the requirements of NOx Technical Code 2008 (NTC 2008) and its applicable appendices

5.2.1 Method of load determination

5.2.2 Estimated accuracy of engine load determination +/- _____ [%] of reading

5.3.1 Method of exhaust gas flow determination

5.3.2 Estimated accuracy of exhaust gas flow determination +/- C-balance _____ [%] of reading

5.4.1 Method of exhaust water content determination

5.4.2 Estimated accuracy of exhaust water content determination +/- --- _____ [%] of reading

5.5.1 Method of fuel mass flow determination

5.5.2 Estimated accuracy of fuel mass flow determination +/- flow meter _____ [%] of reading

5.6.1 Method of O₂ and CO₂ determination

5.6.2 Estimated accuracy of O₂ and CO₂ determination +/- PMD / IRD analyser _____ [%] of reading

6. Measured values for BC determination (to be completed during measurement; measured values)

Date of measurement (dd.mm.yyyy)

16/01/2015				
------------	--	--	--	--

Engine parameters

Measurement at mode points:

100	75	50	25	
-----	----	----	----	--

 [%]
↓ ↓ ↓ ↓ ↓

6.1 Stabilized mode point

Actual Speed

1899	1730	1521	1197	
------	------	------	------	--

 [rpm]
Speed variation during measuring

--	--	--	--	--

 +/- [%]

Actual Load

1000	750	500	250	
------	-----	-----	-----	--

 [kW]
Load variation during measuring

--	--	--	--	--

 +/- [%]

6.2 Charge air temperature

54.4	53.3	53.2	56.8	
------	------	------	------	--

 [°C]

6.3 Charge air pressure

2996	2310	1650	1411	
------	------	------	------	--

 [mbar]

6.4 Exhaust gas temp. at engine outlet

499	506	516	434	
-----	-----	-----	-----	--

 [°C]

6.5 Exh. gas temp. at sampling point

--	--	--	--	--

 [°C]

(only if there is a significant difference to the exhaust gas temperature at the engine outlet)

6.6 Exhaust gas back pressure

--	--	--	--	--

 [mbar]

6.7 Exhaust gas mass flow

5498	3882	2419	1546	
------	------	------	------	--

 [kg/h]

Ambient conditions

6.8 Ambient temp. at engine inlet

25.3	25.2	25.2	24.8	
------	------	------	------	--

 [°C]

6.9 Ambient pressure at engine inlet

960	960	960	960	
-----	-----	-----	-----	--

 [mbar]

6.10 Absolute humidity of ambient air

4.12	4.17	4.25	4.19	
------	------	------	------	--

 [g/kg]

7. Black Carbon Reported as (see 4.3):

FSN

 Unit (see 4.4):

FSN

7.1 Estimated accuracy of measured value

--	--	--	--	--

 +/- [%]

7.2 Black Carbon emission

1.3	1.84	3.2	1.77	
-----	------	-----	------	--

Remark:

--

8. Measurement repeatability Indicators

8.1 95% confidence interval

--	--	--	--	--

(+/- unit measured)

8.2 Variance

--	--	--	--	--

8.3 Sample size

--	--	--	--	--

(number of measurements taken)