

1.15.1 Specific lubrication oil consumption

SLOC: - _____ [g/kWh]

Breaking-in period: ☐ Finished
☐ Not finished
☐ Not applicable

1.15.2 Cylinder liner lubrication

☐ None
☒ Yes, active at

☐ 100% Feed rate: _____ 5207 [g/h]
☐ 75% Feed rate: _____ 3984 [g/h]
☐ 50% Feed rate: _____ 2760 [g/h]
☐ 25% Feed rate: _____ 1627 [g/h]
☐ 10% Feed rate: _____ 812 [g/h]

Breaking-in period: ☒ Finished
☐ Not finished
☐ Not applicable

1.15.3 Inlet valve seat lubrication

☒ None
☐ Yes, active at

☐ 100% Feed rate: - _____ [g/h]
☐ 75% Feed rate: - _____ [g/h]
☐ 50% Feed rate: - _____ [g/h]
☐ 25% Feed rate: - _____ [g/h]
☐ 10% Feed rate: - _____ [g/h]

1.16 Exhaust gas treatment device

☐ None ☒ Yes

☒ SCR
☐ Scrubber
☐ EGR
☐ Water injection
☐ Others: _____

2. Fuel**2.1 Fuel in use**

☐ ULSD ☐ DMX ☐ DMA ☐ DMZ ☐ DMB
☐ RMA ☐ RMB ☐ RMD ☐ RME ☒ RMG ☐ RMK
☐ Other: _____ acc. standard: _____

☐ Natural Gas
☐ Other gases acc. IGF: _____

☐ Liquid to gas fuel ratio as certified at mode point:

100% _____
75% _____
50% _____
25% _____
10% _____

Fuel properties and composition (in use during testing)

2.2 Gas

Please fill in as far as possible
most important marked with *)

Property	Unit / Standard	Actual value	Remark
Methane number*)	[-] / DIN EN 16726		
Lower calorific value*)	[MJ/kg] / ISO 6976		
Higher calorific value	[MJ/kg] / ISO 6976		
Wobbe Indices Ws / Wi	[MJ/m ³] / ISO 6976		
Density*)	[kg/m ³] / ISO 6976		
Methane*)	wt.-% [kg/kg] / ISO 6974 or DIN 51894		
Ethane*)	wt.-% [kg/kg] / ISO 6974 or DIN 51894		
Propane*)	wt.-% [kg/kg] / DIN 51894		
Isobutane*)	wt.-% [kg/kg] / DIN 51894		
N-Butane*)	wt.-% [kg/kg] / DIN 51894		
Pentane	wt.-% [kg/kg] / DIN 51894		
Hexane	wt.-% [kg/kg] / DIN 51894		
Heptane	wt.-% [kg/kg] / DIN 51894		
Nitrogen	wt.-% [kg/kg] / ISO 6974		
Sulphur*)	wt.-% [kg/kg] / ISO 6326-5		
Hydrogen sulfide	wt.-% [kg/kg] / ISO 8819		
Carbon dioxide	wt.-% [kg/kg] / ISO 6974		
Hydrogen	wt.-% [kg/kg] / DIN 51894		
Others			

2.3 Liquid fuel

Please fill in as far as possible
most important marked with *)
essential **)

Property	Unit / Standard	Actual value	Remark
Type of fuel	Grade / ISO 8217	RMG380	
Flash point*)	[°C] / ISO 2719	105	ISO 2719
Viscosity @ 40/50°C **)	[mm ² /s] / ISO 3104	365.1	ISO 3104
Density @ 15°C *)	[kg/m ³] / ISO 3675 or 12185	990.1	ISO 12185
Net calorific value (Hu) *)	[J/g] / DIN 51900	42400	ASTM D 4809
Sulphur content*)	ppm [mg/kg] / ISO 8754 or 14596	2.4	ISO 8754
Ash content*)	ppm [mg/kg] / ISO 6245	57	ISO 6245
Water content*)	ppm [mg/kg] / ISO 3733	1000	ISO 3733
Carbon content*)	wt.-% [kg/kg] / ASTM D5291	85.82	ASTM D5291
Hydrogen content*)	wt.-% [kg/kg] / ASTM D5291	9.58	ASTM D521
Nitrogen content*)	wt.-% [kg/kg] / DIN 51444	0.047	ASTM D 4809
Oxygen content*)	wt.-% [kg/kg] / DIN 51732	1.46	Calc.
Cetane index*)	ISO 4264	-	-
CCAI*)		852	Calc.
FAME content*)	wt.-% [kg/kg] / EN 14078	-	
Mono aromatic compounds*)	wt.-% [kg/kg] / EN 12916	-	
Poly aromatic compounds*)	wt.-% [kg/kg] / EN 12916	-	
Di aromatic compounds	wt.-% [kg/kg] / EN 12916	-	
Tri aromatic compounds	wt.-% [kg/kg] / EN 12916	-	
Inorganic constituents (V)	ppm [mg/kg] / ISO 14597 or 8691	-	
Inorganic constituents (Ni)	ICP	-	
Carbon residues*)	wt.-% [kg/kg] / ASTM D4530	-	
Others			

3. Lube oil properties and composition (in use during testing; Producers specification can be used)

3.1 Circulation lubrication oil

Please fill in as far as possible

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type	BP Energol	
Grade	Multi / Mono	HT30	
BN	mg KOH/g / ISO 3771	8.14	
Ash content	wt.-% [kg/kg] / ISO 6245	-	
Viscosity	[mm ² /s] / ASTM D7042	112.37	at 40°C
Sulphur content	wt.-% [kg/kg] / ISO 20884	0.054945	

3.2 Cylinder oil

Please fill in as far as possible

Please fill in if applicable

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type	BP / CLO	
Grade	Multi / Mono	50M	
BN	mg KOH/g / ISO 3771	70	
Ash content	wt.-% [kg/kg] / ISO 6245		
Viscosity	[mm ² /s] / ASTM D7042		
Sulphur content	wt.-% [kg/kg] / ISO 20884		

3.3 Valve seat lubrication oil

Please fill in as far as possible

Please fill in if applicable

Property	Unit / Standard	Actual value	Remark
Lube oil	Brand / Type		
Grade	multi / mono		
BN	mg KOH/g / ISO 3771		
Ash content	wt.-% [kg/kg] / ISO 6245		
Viscosity	[mm ² /s] / ASTM D7042		
Sulphur content	wt.-% [kg/kg] / ISO 20884		

4. Measurement equipment information (to be completed before measurement) and parameters

Measurement instrument

4.1 BC measurement instrument information Make: AVL Model: 415S

4.2 Measurement principle ☐ LII ☒ FSN ☐ PAS ☐ MAAP
☐ Others: _____

4.3 Values reported as ☐ EC (thermal) Protocol acc.: _____
☐ rBC
☐ eBC
☒ FSN
☐ Others: _____

4.4 Values reported in unit ☐ mg/m_n^3 (wet basis; act. O_2 -concentration) H_2O -conc.: _____ [Vol.-%] (wet)
☐ mg/m_n^3 (dry basis; act. O_2 -concentration)
☐ mg/m_n^3 (dry basis; Ref. O_2 -concentration) O_2 -conc.: _____ [Vol.-%] (dry)
☐ mg/kWh refer to 5.
☒ FSN
☐ mg/kg fuel refer to 5.
☐ Others: _____

4.5 Reference conditions Norm temperature: _____ [°C]
(only if 4.4 is referred to Norm-cubic meters [m_n^3]) Norm pressure: _____ [mbar]

4.6 Sampling time / -number Sampling time of each measurement: _____ 30 [s]
If mean values are reported: Number of consecutive
measurements at each mode point: _____ 5 [-]
Acc. manufacturer specification: ☒ Yes ☐ No

4.7 BC instrument parameter Temperature inside measuring cell: _____ 70 [°C]
Pressure inside measuring cell: _____ Ambient [mbar]
Wavelength(s) used: _____ 550 [nm]
Mass absorption cross section(s) used: _____ 5 [m^2/g]
Conversion equation(s) used: _____ -
Repeatability of the instrument used: _____ $\leq 0.005 \text{ FSN} + 3\%$ of measured value
Reproducibility of the instrument used: _____ $\leq 0.005 \text{ FSN} + 6\%$ of measured value
Acc. manufacturer specification: ☒ Yes ☐ No

Other parameters which could influence the measured values:

Parameter / Correction	Unit

4.8 BC Instrument Calibration

Date of last calibration: - _____ (dd.mm.yyyy)

Calibration procedure according manufacturer specification:

☐ Yes ☐ No ☐ Others: _____

Calibration including zero point: ☐ Yes ☐ No

Used medium for zero point calibration: _____

Used calibration standard: ☐ Synthetic flame soot
☐ Printex-U
☐ Graphite spark aerosol generator GfG soot
☐ Soot with inorganic coatings
☐ Soot without inorganic coatings
☐ Reflectance standards
☐ Others: _____

Remark: _____

Leakage test performed before or after calibration: ☐ Yes ☐ No ☐ Not applicable

4.9 Sample gas pre-treatment

Please fill in if applicable

Exhaust gas dilution: ☐ Yes ☒ No
If yes, dilution ratio (1:x) _____ at mode point: _____ [%]

Dilution medium: ☐ Ambient air ☐ Exhaust gas
☐ Others: _____

Filtration of the dilution medium before dilution: ☐ Yes ☐ No

Temperature of the dilution medium: _____ [°C]

Temperature of the diluted exhaust gas: _____ [°C]

Evaporation tube ☐ Yes ☒ No
Temperature _____ [°C] acc. manufacturer spec. ☐ Yes ☐ No

Catalytic stripper ☐ Yes ☒ No
Temperature _____ [°C] acc. manufacturer spec. ☐ Yes ☐ No

Thermo-denuder ☐ Yes ☒ No
Temperature _____ [°C] acc. manufacturer spec. ☐ Yes ☐ No

Others: _____

4.10 Sample flow rate/volume

Acc. manufacturer specification: ☒ Yes ☐ No

Sample flow rate of the raw exhaust gas: _____ 10 [l/min]

Sample flow rate of the diluted exhaust gas: _____ [l/min]

Sample volume of the raw exhaust gas: _____ [l]

Sample volume of the diluted exhaust gas: _____ [l]

☐ Subkinetic ☐ Isokinetic ☐ Superkinetic ☐ Not applicable

Sample line and probe

4.11 Sample/transfer line

Please fill in if applicable

Use of a sample line: ☒ Yes ☐ No (in situ,...)

Acc. manufacturer specification: ☒ Yes ☐ No

Length of the sample line: 3 [m]

Heated sample line: ☒ Yes ☐ No Temperature: 70 [°C]

Sample line material: Viton

Inner diameter of the sample line: 4 [mm]

Isolated or heated connections between sample line, measurement instrument and probe: ☒ Yes ☐ No

Electrical conductive (sample line material): ☐ Yes ☐ No

Grounded: ☐ Yes ☒ No

Grounding method: _____

Backflushing sample line between measurements: ☒ Yes ☐ No

4.12 Sample probe

Please fill in if applicable

Use of sample probe: ☒ Yes ☐ No (in situ,...)

Acc. manufacturer specification: ☒ Yes ☐ No

Material: ☒ Stainless steel ☐ Others: _____

Type/design:

☐ Probe with single hole at the end (pipe)

☒ Probe with single hole at the end (45° beveled)

☐ Multi-hole

☐ L-shaped pipe with single hole, opening shielded with preclassifier (e.g. hat)

☐ Others: _____

Direction of the probe opening relative to the exhaust gas flow:

☐ With flow ☒ Against flow

☐ Others: _____

Effective cross section of sample hole opening(s) 17.8 [mm²]

Backflushing sample probe between measurements: ☒ Yes ☐ No

Sampling point and probe location

4.13 Sample point and probe location ■ Engine Outlet

☐ Downstream heat exchanger

☐ Downstream exhaust gas treatment device

Treatment device active during measurement ☐ Yes ☐ No

☐ Others: _____

Distance between engine outlet and sampling point: _____ 6 [m]

Diameter of the exhaust gas pipe: _____ 1.002 [m]

Type of exhaust gas pipe where the sample probe is located:

☐ Straight part of the exhaust gas pipe

☐ Bent part of the exhaust gas pipe

Immersion depth of the sample probe: _____ 0.2 [m]

Orientation of the exhaust gas pipe where the sample probe is located:

☐ Horizontal ☐ Vertical ■ Others: _____ downward

Length of straight part of the exhaust gas pipe,

if sample probe is located at straight part of the exhaust gas pipe:

Upstream sample probe: _____ 4 [m]

Downstream sample probe: _____ 1 [m]

Exhaust gas pulsation at the sampling point during measurement:

■ No ☐ Yes _____ [mbar]

5. Determination of engine load, exhaust gas flow, exhaust water content, fuel mass flow, O₂ and CO₂ (if applicable)

5.1 Determination of values, instrument performance and calibration shall be in accordance with the requirements of NOx Technical Code 2008 (NTC 2008) and its applicable appendices

5.2.1 Method of load determination

Electrical WB Signal 4-20mA

5.2.2 Estimated accuracy of engine load determination

+/- 1 [%] of reading

5.3.1 Method of exhaust gas flow determination

Calculation

5.3.2 Estimated accuracy of exhaust gas flow determination

+/- 1 [%] of reading

5.4.1 Method of exhaust water content determination

Calculation

5.4.2 Estimated accuracy of exhaust water content determination

+/- 1 [%] of reading

5.5.1 Method of fuel mass flow determination

Load Cells

5.5.2 Estimated accuracy of fuel mass flow determination

+/- < 1 [%] of reading

5.6.1 Method of O₂ and CO₂ determination

Horiba 7170H

5.6.2 Estimated accuracy of O₂ and CO₂ determination

+/- < 1 [%] of reading

6. Measured values for BC determination (to be completed during measurement; measured values)

Date of measurement (dd.mm.yyyy)

21.09.2015	21.09.2015	21.09.2015	21.09.2015	
------------	------------	------------	------------	--

Engine parameters

Measurement at mode points:

100	75	50	25	
-----	----	----	----	--

 [%]

	↓	↓	↓	↓	↓	
6.1 Stabilized mode point						
Actual Speed	105.5	95.6	83.9	66.6		[rpm]
Speed variation during measuring	1	1	1	1		+/- [%]
Actual Load	6509	4892	3271	1632		[kW]
Load variation during measuring	1	1	1	1		+/- [%]
6.2 Charge air temperature	36	36.6	29.6	29		[°C]
6.3 Charge air pressure	3630.000	2730.000	1650.000	9.680		[mbar]
6.4 Exhaust gas temp. at engine outlet	263	222	218	247		[°C]
6.5 Exh. gas temp. at sampling point	254	217	211	231		[°C]
(only if there is a significant difference to the exhaust gas temperature at the engine outlet)						
6.6 Exhaust gas back pressure	35.31	27.87	18.58	9.68		[mbar]
6.7 Exhaust gas mass flow	47144.000	38083.000	28117.000	15048.000		[kg/h]
Ambient conditions						
6.8 Ambient temp. at engine inlet	20.6	18.7	17.2	17.2		[°C]
6.9 Ambient pressure at engine inlet	963.29	962.73	961.55	960.55		[mbar]
6.10 Absolute humidity of ambient air	10.9	10.1	9.9	7.9		[g/kg]
7. Black Carbon						
				FSN		
7.1 Estimated accuracy of measured value	5	5	5	5		+/- [%]
7.2 Black Carbon emission	0.097	0.112	0.099	0.12		
Remark: _____						
8. Measurement repeatability Indicators						
8.1 95% confidence interval (+/- unit measured)	-	-	-	-		
8.2 Variance	-	-	-	-		
8.3 Sample size (number of measurements taken)	5	5	5	5		